



# **ci c40** *emthermic*



# The pressure washer with a Rato motor for maximum results, even in the most extreme conditions

The CI C40 EM THERMIC is the cold pressure washer with a combustion engine designed to guarantee maximum results, even in the most extreme conditions. The powerful Rato motor makes it the professional high-pressure washer that is perfect for jobs where you cannot connect to the mains electricity, therefore ideal for continuous jobs.

Equipped with a robust ergonomic frame that offers excellent protection for the mechanical parts, the CI C40 EM THERMIC is also compact and easy to transport. At the same time, the inflatable tires and wide rubber treads guarantee extreme manoeuvrability for the pressure washer, even over uneven surfaces.

Powered by gasoline, the CI C40 EM THERMIC is a robust pressure washer that is perfect for heavy, continuous use. It is therefore the ideal solution for the most demanding cleaning in the agricultural, industrial, or building sectors, or for all situations in which high performance and manoeuvrability is required.

## THE ADVANTAGES OF CI C40 EM THERMIC

Many are the benefits CI C40 EM THERMIC can offer:

- Pressure washer with robust trolley, two inflatable wheels and anti-vibration feet that facilitate manoeuvrability and transportability
- Corrosion-resistant painted steel frame and practical handle to facilitate movement
- Powerful Rato motor with valves at the head, low operating temperature and high reliability, durability and oil savings, making the pressure washer perfect for professional applications
- Motor with oil sensor and inspectionable oil levels
- Drain plugs and holes to facilitate maintenance and oil changes
- Ceramic 3-piston pump with crank-rod system and brass head for high performance
- Automatic accelerator regulator
- Automatic safety valve
- Adjustable pressure
- Heat valve
- Built-in detergent suction
- Inspectionable water feed filter
- Practical built-in 2.8-litre detergent tank
- Anti-vibration feet to reduce vibrations and noise level
- Comes with professional accessories: gun with protection and Swivel coupling, lance with rotating nozzle, lance with interchangeable nozzle
- Black nozzle for low pressure – 65°
- Red nozzle – straight jet – 0°
- Yellow nozzle – fan jet – 15°
- White nozzle – fan jet – 40°
- 10-metre reinforced high pressure tube
- Accessory holder and tube storage on the back

TECHNICAL DESCRIPTION		CI C40 EM THERMIC
Max pressure	bar/psi	280/4060
Max flow rate	l/h	960
Type	-	cold water
Motor	type/hp	Rato/10,2 combustion
Rotation speed	rpm	3400
Pump	type	ceramic piston with crank-rod system
Pump head	material	brass
Net weight	Kg	58,4
Machine dimensions (Lxhxw)	mm	900x900x530



COMAC S.p.A. Via Maestri del Lavoro, 13 - 37059 Santa Maria di Zevio - Verona - ITALY  
Tel. 045 8774222 - [www.comac.it](http://www.comac.it) - [com@comac.it](mailto:com@comac.it)

Comac S.p.A. org. cert. ISO 9001:2015, ISO 14001:2015, ISO 45001:2018, SA 8000:2014

